



mlBibTeX Meets ConTeXt

Jean-Michel Huffer

► To cite this version:

| Jean-Michel Huffer. mlBibTeX Meets ConTeXt. TUGB, 2006, pp.76–82. hal-00644461

HAL Id: hal-00644461

<https://hal.science/hal-00644461>

Submitted on 24 Nov 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

MLBibTeX meets ConTeXt

JEAN-MICHEL HUFFLEN

LIFC (FRE CNRS 2661)

University of Franche-Comté

16, route de Gray

25030 Besançon Cedex, France

hufflen (at) lifc dot univ dash fcomte dot fr

<http://lifc.univ-fcomte.fr/~hufflen>

Abstract

This article reports a first experiment of using MLBibTeX — our reimplementa-tion of BibTeX — with ConTeXt, a TeX format more modern than L^ATeX. We show how to take as much advantage as possible of both ConTeXt and MLBibTeX features when they are used together. Also, many end-users are accustomed to using L^ATeX commands inside values of BibTeX fields, and such commands may be unrecognised by ConTeXt. We explain how patterns and preambles allow us to solve such problems.

Keywords

ConTeXt, bib module, bibliographies, bibliography styles, BibTeX, MLBibTeX.

Introduction

Listing the bibliographical references cited within a document can be done manually — if the L^ATeX word processor is used, that consists of typing successive `\bibitem` commands of a `thebibliography` environment [18, § 4.3.2] — but such an approach leads to texts difficult to maintain and reuse, because they are tightly bound to *bibliography styles*. A publisher or anthology editor might like authors' last names of a 'References' section to be typeset using small capitals, whereas another publisher would require the use of standard Roman letters for these last names. Likewise, first names may be abbreviated or put *in extenso*, w.r.t. the bibliography style used. In addition, doing a document's bibliography manually is error-prone: if this bibliography is *unsorted*, that is, if the order of items is the order of first citations of these items throughout the document, some change within the document's body can cause the bibliography to be reorganised. Likewise, keys based on the author-date system [19, § 12.3] may need to be recomputed if the bibliography is enriched.

A better method is to use a *bibliography processor*: such a program is given *citation keys*, searches bibliography database files for resources associated with these keys, and arranges them according to a bibliography

style, the result being a source file for a 'References' section, suitable for a word processor. A well-known association between a word and bibliography processor is given by L^ATeX and BibTeX [21], working in tandem, although this example is not unique. As another example, Tib [1] has sometimes been used with *Plain TeX* [17]; more generally, other examples of bibliography processors are given in [25].

'Historically', BibTeX was initially designed to work with Scribe¹ [24]. In fact, only a few points related to TeX are hard-wired within BibTeX: using braces as delimiters, considering a group such as `{\command ...}` as an accent command applied to arguments in order to produce a single character [19, § 13.2.2], the use of the '~' character for unbreakable spaces when names are formatted [20, § 5.4], the `width$` function, provided by the style language, that returns the width of a string, expressed using TeX units [19, Table 13.8]. Thus bibliographic entries specified with BibTeX should be usable with any *format* built from TeX, provided that end-users do not put L^ATeX-specific commands inside field values. Let us recall that TeX basically provides a powerful framework

¹That is why BibTeX uses the '@' character for specifying its commands and entry types: this character introduces a command name in Scribe, like '\ ' in TeX. This convention is also used within Texinfo [3], the GNU documentation format.

```
@BOOK{meaney2003,
  AUTHOR = {John Meaney},
  TITLE = {Context},
  PUBLISHER = {Bantam Books},
  YEAR = 2003,
  NUMBER = 2,
  SERIES = {The \emph{Nulapeiron}
    Sequence},
  NOTE = {The Sequel to ‘‘Paradox’’.
    [Pas de version française
    connue!] ! french},
  LANGUAGE = english}
```

Figure 1: Example of a bibliographical entry.

to format texts nicely, but to be fit for use, the definitions of this framework need to be organised in a format. The first formats were *Plain T_EX* and *L^AT_EX*; another format, more modern, is ConT_EXt [5]. A bibliographic module, usable in conjunction with BibT_EX, has been added to ConT_EXt [6, 8]. This module defines ConT_EXt commands to deal with the components (metadata) of bibliographical information.²

Over the last few years, we have designed and implemented a ‘new BibT_EX’ — MLBibT_EX, for ‘MultiLingual BibT_EX’. Of course, it has been designed to work with L^AT_EX, but we plan to use it for other output formats, too [10]. This article is a revised and extended version associated with the presentation given at EuroT_EX. It aims to report a first experiment of using MLBibT_EX to build outputs suitable for ConT_EXt.³ First, we show how ConT_EXt can be easily used to pretty-print bibliography database (.bib) files. Then we explain how an interface between ConT_EXt and BibT_EX can be improved when MLBibT_EX is used. This article should be read without any difficulty by any user familiar with L^AT_EX and BibT_EX: it requires only basic knowledge of ConT_EXt and its bib module. It also refers to some basic notions of XML⁴ and Scheme, the implementation language for MLBibT_EX.⁵

²If we compare this module to what is provided for L^AT_EX, its approach is close to the `jurabib` package [19, § 12.5.1], in the sense that items of bibliographical information are given as arguments of new commands. If you would like to redefine the layout of a bibliography’s items, just redefine these new commands.

³We have used the most recent version of ConT_EXt at the time of writing, included in T_EX Live 2005, available on DVD-ROM.

⁴EXtensible Markup Language. Readers interested in an introductory book to this formalism can consult [23].

⁵The version used is described in [14].

```
<mlbiblio>
...
<book id="meaney2003" language="english">
...
  <series>
    The <emph>Nulapeiron</emph> Sequence
  </series>
  <note>
    The Sequel to
    <emph emf="no" quotedf="yes">
      Paradox
    </emph>.
    <group language="french">
      Pas de version française connue!
    </group>
  </note>
</book>
...
</mlbiblio>
```

Figure 2: XML tree for the bibliographical entry shown in Figure 1.

Pretty-print bibliographies

MLBibT_EX’s new syntactic features for bibliographical entries are detailed in [9]. Roughly speaking, any .bib file suitable for ‘old’ BibT_EX can be processed by MLBibT_EX, except that square brackets are ordinary characters for the former, syntactic delimiters for the latter. Figure 1 gives an example of a bibliographical entry for a book written in English (the value of the LANGUAGE field, handled by MLBibT_EX). The value of the NOTE field includes a text to be put down only in French-speaking bibliographies, this text being enclosed by square brackets and labelled by the french language identifier.

As mentioned in [9], the result of parsing a .bib file can be viewed as an XML tree. For example, parsing a file containing the meaney2003 entry results in the XML tree sketched in Figure 2. Such a tree can be saved into a file and displayed *verbatim* or handled by tools belonging to XML’s world. ConT_EXt provides a way to handle XML texts [22], so it can deal with such files. Figure 3 sketches a pretty-printer for bibliographical entries by means of ConT_EXt commands documented in [7, 22], other basic T_EX commands — such as `\expandafter` or `\uppercase` — being documented in [17]. These bibliographical entries are displayed using MLBibT_EX’s syntax. In addition, MLBibT_EX’s new syntax for emphasising the parts of per-

```

\enableregime[i11]

\def\ProcessMlBibTeXFieldName[#1]{\tt \expandafter\uppercase{#1} = \textbraceleft}}
\def\CloseMlBibTeXFieldValue{\tt \textbraceright},\par}
\def\ProcessMlBibTeXLanguagePart[#1]{\PutLanguageCommand[#1]{\tt LANGUAGE =} #1,\par}
\def\ProcessMlBibTeXNamePart[#1]{\tt #1 => }
\def\PutLanguageCommand[#1]{\doifelse{#1}{english}{\language[en]}{%
  \doifelse{#1}{french}{\language[fr]}{\doif{#1}{magyar}{\language[hu]}{}}}

\defineXMLenvironment[mlbiblio] \startitemize \stopitemize
\defineXMLenvironment[book] {\item {\tt @BOOK\textbraceleft}\XMLpar{book}{id}{*unkeyed*},%
  \startnarrower[left] \ProcessMlBibTeXLanguagePart[\XMLpar{book}{language}{english}] }{%
  \stopnarrower {\tt \textbraceright}}
...
\defineXMLenvironment[author] {\ProcessMlBibTeXFieldName[author]} \CloseMlBibTeXFieldValue
...
\defineXMLenvironment[first] {\ProcessMlBibTeXNamePart[first]} {, }
\defineXMLenvironment[von] {\ProcessMlBibTeXNamePart[von]} {, }
\defineXMLenvironment[last] {\ProcessMlBibTeXNamePart[last]} \unskip
\defineXMLenvironment[junior] {, \ProcessMlBibTeXNamePart[junior]} \unskip

\defineXMLenvironment[asitis] {\tt \textbraceleft} {\tt \textbraceright}}
\defineXMLenvironment[emph] {\doifelse{emph}{quotedf}{yes}{\tt ‘}{%
  \doifelse{emph}{emf}{yes}{\tt \textbackslash emph\textbraceleft}\bgroup\em}{}} {%
  \doifelse{emph}{emf}{yes}{\tt \textbraceright}\egroup}{%
  \doifelse{emph}{quotedf}{yes}{\tt ’}{}}}

\def\GroupMarker{! }
\defineXMLenvironment[foreigngroup] {\tt []%
  \bgroup\PutLanguageCommand[\XMLpar{foreigngroup}{language}{*error*}] }{%
  \egroup{\tt ] : \XMLpar{foreigngroup}{language}{*error*}} }
\defineXMLenvironment[group] {\startnarrower[left]{\tt []%
  \bgroup\PutLanguageCommand[\XMLpar{group}{language}{*error*}] }{%
  \egroup{\tt ] \GroupMarker \XMLpar{group}{language}{*error*}} \stopnarrower}
\defineXMLenvironment[nonemptyinformation] {\tt []}\def\GroupMarker{* } {}

\starttext
\processXMLfilegrouped{...}
\stoptext

```

Figure 3: Pretty-printing an XML tree resulting from parsing .bib files.

son names [21, § 4], based on keywords, is used. For example:

AUTHOR = {first => John, last => Meaney},

We can notice that keywords, syntactic delimiters, and field names are typeset using a typewriter font, whereas the Roman typeface is used for metadata. As another pretty-printing feature, typographical effects are put into action. For example, the value of the SERIES field will be rendered as follows:

SERIES = {The \emph{Nulapeiron} Sequence},

Likewise, any information is typeset using the typographical conventions of its own language:

NOTE =

{ ... [Pas de version française connue!] ... }

where the exclamation mark is preceded by a thin space character, as in French.

If we look at the text given in Figure 3, we notice that the only heavy part concerns *language identifiers*. ConTeXt uses ISO codes for languages [5, Ch. 7] and can switch to any language via the `\language[...]` command, without any preliminary declaration such as L^AT_EX needs when the babel package is loaded [19, § 9.2]. MlBibTeX’s language identifiers are unambiguous prefixes of packages or options of the babel package, as explained in [12]. For example:

- `polish` is for the option of the `babel` package,
- `polSKI` is for the `polSKI` package [4, App. F],
- `pol` is for either of these last two, the final choice depends on what a user puts in the document's preamble,
- `po` is ambiguous because it may be the prefix of 'Polish' or 'Portuguese'.

In fact, we need a complete correspondence table, with our `\PutLanguageCommand` command given in Figure 3 implementing it only partially.⁶ Let us remark that such a correspondence table could be useful for other purposes, e.g., generating bibliographies for documents written using DocBook⁷ [27]. This table between the structure managing MLBibTeX's language identifiers [12] and ISO codes for languages [2] has been implemented within the Scheme functions of MLBibTeX.⁸

Figure 3 gives a rough version of such a pretty-printer, which may be improved.⁹ For example, the error cases are just labelled within the source text by identifiers surrounded by '*', which could be refined into a more efficient marking of errors. We can also align '=' signs vertically between field names and values. That can be done in a tabulate environment, but leads to slightly complicated ConTeXt commands, because we need to collect the content of a table before formatting it.

ConTeXt and MLBibTeX together

If you would like BibTeX to generate specifications of publications suitable for ConTeXt from bibliographical entries, you may use the `\setupbibtex` command, as explained in [8, § 2.4]. This command gets access to bibliography styles suitable for ConTeXt, that is, handled by the `bib` module. Since MLBibTeX can process bibliography styles using the `bst` language [20] in compatibility mode [13], it can deal with these styles.

⁶In fact, this `\PutLanguageCommand` command could be written in an easier way, since complete names such as `english`, `french`, ... also work as arguments of the `\language` command of ConTeXt. However, this feature is not described in [5].

⁷DocBook is an XML-based system for writing structured documents.

⁸How to put this implementation into action is shown in Figure 4.

⁹A more elaborated version can be downloaded from MLBibTeX's home page: <http://lifc.univ-fcomte.fr/~hufflen/texts/mlbibtex/contextstuff/>.

However, we do not recommend this solution, which should be temporary, from our point of view. In addition, the compatibility mode is not very efficient for sake of implementation issues.¹⁰ A first improvement could be the development of new bibliography styles, using the `nbst`¹¹ language, close to XSLT¹² [26] and described in [9].

As mentioned in [19, § 13.5.2], the choices among different styles for displaying person names, work titles, ... causes a combinatorial explosion. Besides, all the functions of a bibliography style of BibTeX must be grouped into a unique file, so a rich library of bibliography styles for BibTeX should include a huge number of styles, each being monolithic. As explained in [11], several fragments of a bibliography style written using the `nbst` language can be assembled dynamically, provided that there is no conflict among the templates programmed using `nbst`. Consequently, designing styles according to a modular approach is easier in MLBibTeX than in BibTeX. Moreover, an extended version of the `\setupbibtex` command could allow the use of *several complementary files* for a bibliography style.

ConTeXt vs L^ATeX

End users sometimes put L^ATeX commands within the values of BibTeX fields. Some commands aim to increase the expressive power of the information put into `.bib` files, an example being given by the value of the `SERIES` field in Figure 1. Other examples are related to some features of BibTeX:

`{Maria {\MakeUppercase{d}e La} Cruz}`
—given in [19, p. 767] about person names—allows BibTeX to interpret '{de La}' as a particle,¹³ because this group, surrounded by braces, begins with a lowercase letter, even if this particle should be typeset as 'De La'. Some commands are recognised by ConTeXt, some not. There are two solutions to this problem:

- when outputs for ConTeXt are produced, the contents of `@preamble` rubrics included in `.bib` files

¹⁰When MLBibTeX parses a `.bib` file, it tries to organise information into a deep tree, as far as possible. For example, the components of a person name are split into subtrees. When the compatibility mode is used, these components are serialised into a string, and destructured again by the `format.name$` function of `bst` [20].

¹¹New Bibliography STyles.

¹²eXtensible Stylesheet Language Transformations, the language of transformations used for XML texts.

¹³'Maria' being the first name, 'Cruz' the last name.

```

(and-let* (((log-output-p-pv 'open) jobname))           ; Opening the log (.mblg) file.
  (((bibtexkey-alist-pv 'add-key) "hoekwater2001"))    ; Citation key to be processed.
  ...
  (((bibtexkey-alist-pv 'extend)))                     ; If we want to process all the entries (\nocite{*}).
  (let ((bib-suffix ".bib"))
    (every (lambda (filename) ; Parsing .bib files. If the suffix is not given, the filename-plus
              ; function adds it.
              (s-parse-bib-file (filename-plus filename bib-suffix #f)))
            bibliographyfilename-list)))
  (sxml-mlbiblio-tree (s-get-sxml-mlbiblio-tree)) ; Build the SXML tree.
  (((language-trie-pv 'use-iso-code-table))) ; Using ISO codes for all the languages.
  (((preamble-pv 'set) "contextpreamble")) ; Using @contextpreamble{...} as preambles.
  (k1 (n-assemble-nstyles stylefilename-list)) ; Styles are assembled and compiled into a
                                              ; so-called k1 function.
  (((output-encoding-pv 'set) 'latin1)) ; Accented letters of Latin-1 allowed in the output file.
  (((bbl-output-p-pv 'open) jobname))) ; Opening the output file.
(k1 sxml-mlbiblio-tree) ; Applying the whole style to the SXML tree.
((bbl-output-p-pv 'close)) ; Closing files.
((log-output-p-pv 'close))
#t) ; Final result.

```

Figure 4: MLBibTeX's kernel for use with ConTeXt.

are not written as BibTeX would do; instead, MLBibTeX uses @contextpreamble rubrics,¹⁴ which can be used to implement some L^AT_EX commands in ConTeXt; switching to another preamble is controlled by an option of the MLBibTeX program;¹⁵

- a better solution is given by *patterns*, expressed in Scheme, replacing substrings by XML-conformant strings; for example:¹⁶

```

(define-pattern "\\emph{#1}"
  "<emph>#1</emph>")

```

Patterns aim to process any L^AT_EX command included in a .bib file, including user-defined commands, as explained in [10]. ‘General’ patterns are planned for the next version, only some pre-defined patterns are implemented now, mostly for letters accented by means of T_EX commands.¹⁷

¹⁴This new command does not interfere with parsing .bib files by ‘old’ BibTeX, because it looks like:

@...{<string> (# <string>)*}
 where ‘<string>’ is surrounded by braces or double quotes. Such a command is ignored by ‘old’ BibTeX.

¹⁵... or see how to process in Scheme in Figure 4.

¹⁶Let us recall that in Scheme, the ‘\’ character is used to escape special characters in constant strings. To include it within a string, it must be itself escaped.

¹⁷The internal representation uses Latin-1, accented letters of this encoding being viewed as single characters.

This solution is more general, not limited to bibliographies usable by ConTeXt. Let us assume that you have to convert a .bib file into HTML,¹⁸ and consider the following title:

\ConTeXt, the Manual

Even if displaying ‘\ConTeXt’ on a Web page does not cause any error, it is better to introduce this pattern:

```

(define-pattern "\\ConTeXt"
  "<symbol name='ConTeXt' />")

```

Now you can define a way to display this symbol within a bibliography style.

Direct interface

ConTeXt does not deal with the same auxiliary files as L^AT_EX. Moreover, it builds an .aux file only if the \setupbibtex command is activated. Let us recall that BibTeX reads only .aux files, never .tex files. However, MLBibTeX may need to parse the preamble of a source file, as explained in [12]. Concerning outputs suitable for ConTeXt, the information of interest is the encoding: can MLBibTeX put accented letters of Latin-1 directly into the resulting file? Or does it have to use T_EX accent commands?

¹⁸HyperText Markup Language.

A better solution than making useless `.aux` files and the parsing of preambles of Con \TeX t documents (parts between the beginning of a document and the `\starttext` command) is to build a *driver* directly written in Scheme. Of course, this task requires some knowledge of both the Scheme programming language and the broad outlines of MLBib \TeX 's implementation, but the result is a small-sized program, as shown in Figure 4. You can see how to add a citation key as if it were caught from an `.aux` file, and how to get all the entries of `.bib` files as the `\nocite{*}` command of L \TeX would cause to. We also show how to use a preamble command `—@...{...}`—specific for Con \TeX t. Other information to be supplied is:

jobname (string) the base name of the main input file processed by Con \TeX t;

bibliographyfilename-list (string list) all of the `.bib` file names to be searched;

stylefilename-list (string list) all the fragments of a bibliography style.

The `and-let*` macro [15] causes the sequential evaluation of the clauses of its first argument to be stopped as soon as a false value (for a failure) is returned. For example, the evaluation of the whole expression given in Figure 4 stops and returns the false value if a log file (`.mblg` file) cannot be opened. Otherwise, the non-false result of a clause may become the value of a local variable. For example, the `sxml-biblio-tree` variable is given the bibliographical entries in the SXML¹⁹ format. Then the other arguments of the `and-let*` macro are evaluated sequentially if all the clauses succeed, that is, if there is no error in parsing `.bib` files and building the bibliography style. In our case, the style—which results in a Scheme function—is applied to the bibliographical entries, and output files are closed. Finally, the true value is returned.

Going further, the `texexec` script, which launches successive run phases of Con \TeX t, could be extended to launch the MLBib \TeX program.

Conclusion

When we began this task, we had written only some small-sized examples using Con \TeX t and emphasising its differences with L \TeX . And we were afraid we

would have to reprogram some important parts of MLBib \TeX . To be honest, changes were needed, but not as many as we believed. Concerning the `bib` module, we learned it more quickly than we planned. The first meeting between MLBib \TeX and Con \TeX t has succeeded.

Acknowledgements

Many thanks to Hans Hagen and Taco Hoekwater, who kindly answered my very Con \TeX t-nical questions. I am also grateful to Karl Berry, who proofread this article.

References

- [1] James C. Alexander: *Tib: a \TeX Bibliographic Preprocessor*. Version 2.2, see CTAN: `biblios/tib/tibdoc.tex`. 1989.
- [2] Harald Tveit Alvestrand: *Request for Comments: 1766. Tags for the Identification of Languages*. UNINETT, Network Working Group. March 1995. <http://www.cis.ohio-state.edu/cgi-bin/rfc/rfc1766.html>.
- [3] Robert J. Chassell and Richard M. Stallman: *Texinfo. The GNU Documentation System. Version 4.8*. <http://www.gnu.org/software/texinfo>. December 2004.
- [4] Antoni Diller: *L \TeX wiersz po wierszu*. Wydawnictwo Helio, Gliwice. Polish translation of *L \TeX Line by Line* with an additional annex by Jan Jelowicki. 2001.
- [5] Hans Hagen: *Con \TeX t, the Manual*. November 2001. <http://www.pragma-ade.com/general/manuals/cont-enp.pdf>.
- [6] Taco Hoekwater: “The Bibliographic Module for Con \TeX t”. In: *Euro \TeX 2001*, pp. 61–73. Kerkrade (the Netherlands). September 2001.
- [7] Taco Hoekwater: *Con \TeX t System Macros. Part 1: General Macros*. 2002. <http://tex.aanhet.net/context/syst-gen-doc.pdf>.
- [8] Taco Hoekwater: *Con \TeX t. Module Documentation*. March 2006. <http://dl.contextgarden.net/modules/t-bib/doc/context/bib/bibmod-doc.pdf>.

¹⁹Scheme implementation of XML. See [16] for more information.

- [9] Jean-Michel Huppen: “MLBibTeX’s Version 1.3”. *TUGboat*, Vol. 24, no. 2, pp. 249–262. July 2003.
- [10] Jean-Michel Huppen: “MLBibTeX: beyond L^AT_EX”. In: Karl Berry, Baden Hughes and Steven Peter, eds., *Preprints for the 2004 Annual Meetings*, pp. 77–84. TUG, Xanthi, Greece. August 2004.
- [11] Jean-Michel Huppen: “Making MLBibTeX Fit for a Particular Language. Example of the Polish Language”. *Biuletyn GUST*, Vol. 21, pp. 14–26. 2004.
- [12] Jean-Michel Huppen: *Managing Languages within MLBibTeX*. To appear. June 2005.
- [13] Jean-Michel Huppen: “BibTeX, MLBibTeX and Bibliography Styles”. *Biuletyn GUST*, Vol. 23, pp. 76–80. In *BachTeX 2006 conference*. April 2006.
- [14] Richard Kelsey, William D. Clinger, Jonathan A. Rees, Harold Abelson, Norman I. Adams IV, David H. Bartley, Gary Brooks, R. Kent Dybvig, Daniel P. Friedman, Robert Halstead, Chris Hanson, Christopher T. Haynes, Eugene Edmund Kohlbecker, Jr, Donald Oxley, Kent M. Pitman, Guillermo J. Rozas, Guy Lewis Steele, Jr, Gerald Jay Sussman and Mitchell Wand: “Revised⁵ Report on the Algorithmic Language Scheme”. *HOSC*, Vol. 11, no. 1, pp. 7–105. August 1998.
- [15] Oleg B. Kiselyov: *and-let*: an and with local bindings, a guarded let* special form*. March 1999. <http://srfi.schemers.org/srfi-2/>.
- [16] Oleg E. Kiselyov: *XML and Scheme*. September 2005. <http://okmij.org/ftp/Scheme/xml.html>.
- [17] Donald Ervin Knuth: *Computers & Typesetting. Vol. A: The TeXbook*. Addison-Wesley Publishing Company, Reading, Massachusetts. 1984.
- [18] Leslie Lamport: *L^AT_EX. A Document Preparation System. User’s Guide and Reference Manual*. Addison-Wesley Publishing Company, Reading, Massachusetts. 1994.
- [19] Frank Mittelbach and Michel Goossens, with Joannes Braams, David Carlisle, Chris A. Rowley, Christine Detig and Joachim Schrod: *The L^AT_EX Companion*. 2nd edition. Addison-Wesley Publishing Company, Reading, Massachusetts. August 2004.
- [20] Oren Patashnik: *Designing BibTeX Styles*. February 1988. Part of the BibTeX distribution.
- [21] Oren Patashnik: *BibTeXing*. February 1988. Part of the BibTeX distribution.
- [22] PRAGMA ADE, <http://www.pragma-ade.com/general/manuals/example.pdf>: *XML in ConTeXt*. November 2001.
- [23] Erik T. Ray: *Learning XML*. O’Reilly & Associates, Inc. January 2001.
- [24] Brian Keith Reid: *SCRIBE Document Production System User Manual*. Technical Report, Unilogic, Ltd. 1984.
- [25] David Rhead: *The “Operational Requirement” (?) for Support of Bibliographic References by L^AT_EX 3*. Technical Report L3–005, L^AT_EX 3. August 1993.
- [26] W3C: *XSL Transformations (XSLT). Version 1.0*. W3C Recommendation. Edited by James Clark. November 1999. <http://www.w3.org/TR/1999/REC-xslt-19991116>.
- [27] Norman Walsh and Leonard Mueller: *DocBook: The Definitive Guide*. O’Reilly & Associates, Inc. October 1999.